

UNCLASSIFIED



**zOS BMC CONTROL-0 for
RACF STIG**

Version: 7

Release: 2

03 Mar 2026

Description:

Group ID (Vulid): V-18014**Group Title:** ZB000040**Rule ID:** SV-32004r1_rule**Severity:** CAT II**Rule Version (STIG-ID):** [ZCTO0040](#)**Rule Title:** BMC CONTROL-O configuration/parameter values are not specified properly.

Vulnerability Discussion: BMC CONTROL-O configuration/parameters control the security and operational characteristics of products. If these parameter values are improperly specified, security and operational controls may be weakened. This exposure may threaten the availability of the product applications, and compromise the confidentiality of customer data.

IAControls: ECCD-1, ECCD-2**Check Content:**

Ensure the following keywords are specified in the BMC CONTROL-O security parameter member:

Keyword Value

DEFMCHKO \$\$CTOEDM
SECTOLO NO
DFMO01 EXTEND
DFMO02 EXTEND
DFMO03 EXTEND
DFMO04 EXTEND
DFMO08 EXTEND
DFMO10 PROD (new for 6.3.xx)
DFMO15 EXTEND

Fix Text: The BMC CONTROL-O Systems programmer will verify that any configuration/parameters that are required to control the security of the product are properly configured and syntactically correct. Set the standard values for the BMC CONTROL-O security parameters for the specific ACP environment along with additional IOA security parameters with standard values as documented below.

Keyword Value
DEFMCHKO \$\$CTOEDM
SECTOLO NO
DFMO01 EXTEND
DFMO02 EXTEND
DFMO03 EXTEND
DFMO04 EXTEND
DFMO08 EXTEND
DFMO10 PROD (new for 6.3.xx)
DFMO15 EXTEND

CCI: CCI-000035

Group ID (Vulid): V-22689

Group Title: ZB000041

Rule ID: SV-32006r1_rule

Severity: CAT II

Rule Version (STIG-ID): [ZCTO0041](#)

Rule Title: BMC CONTROL-O configuration/parameter values are not specified properly.

Vulnerability Discussion: BMC CONTROL-O configuration/parameters control the security and operational characteristics of products. If these parameter values are improperly specified, security and operational controls may be weakened. This exposure may threaten the availability of the product applications, and compromise the confidentiality of customer data.

IAControls: ECCD-1, ECCD-2

Check Content:

The following keywords will have the specified values in the BMC CONTROL-O security parameter member:

Keyword Value

RUNTDFT OWNER

RUNTCACH 100

AUTOMLOG V

Fix Text: The BMC CONTROL-O Systems programmer will verify that any configuration/parameters that are required to control the security of the product are properly configured and

syntactically correct. Set the standard values for the BMC CONTROL-O security parameters for the specific ACP environment along with additional IOA security parameters with standard values as documented below.

Keyword Value
RUNTDFT OWNER
RUNTCACH 100
AUTOMLOG V

CCI: CCI-000035

Group ID (Vulid): V-17985

Group Title: ZB000060

Rule ID: SV-32016r1_rule

Severity: CAT II

Rule Version (STIG-ID): [ZCTO0060](#)

Rule Title: BMC CONTROL-O security exits are not installed or configured properly.

Vulnerability Discussion: The BMC CONTROL-O security exits enable access authorization checking to BMC CONTROL-O commands, features, and online functionality. If these exit(s) is (are) not in place, activities by unauthorized users may result. BMC CONTROL-O security exit(s) interface with the ACP. If an unauthorized exit was introduced into the operating environment, system security could be weakened or bypassed. These exposures may result in the compromise of the operating system environment, ACP, and customer data.

IAControls: DCCS-1, DCCS-2, ECSD-1, ECSD-2

Check Content:

Interview the systems programmer responsible for the BMC CONTROL-O. Determine if the site has modified the following security exit(s)::

CTOSE01

CTOSE02

CTOSE03

CTOSE04

CTOSE08

CTOSE10

CTOSE15

Ensure the above security exit(s) has (have) not been modified.

If the above security exit(s) has (have) been modified, ensure that the security exit(s) has (have) been approved by the site systems programmer and the approval is on file for examination.

Fix Text: The System programmer responsible for the BMC CONTROL-O will review the BMC CONTROL-O operating environment. Ensure that the following security exit(s) is (are) installed properly. Determine if the site has modified the following security exit(s):

CTOSE01

CTOSE02

CTOSE03

CTOSE04
CTOSE08
CTOSE10
CTOSE15

Ensure that the security exit(s) has (have) not been modified.

If the security exit(s) has (have) been modified, ensure the security exit(s) has (have) been checked as to not violate any security integrity within the system and approval documentation is on file.

CCI: CCI-000035

Group ID (Vulid): V-16932

Group Title: ZB000000

Rule ID: SV-31908r1_rule

Severity: CAT II

Rule Version (STIG-ID): [ZCTOR000](#)

Rule Title: BMC CONTROL-O installation data sets are not properly protected.

Vulnerability Discussion: BMC CONTROL-O installation data sets have the ability to use privileged functions and/or have access to sensitive data. Failure to properly restrict access to these data sets could result in violating the integrity of the base product which could result in compromising the operating system or sensitive data.

IAControls: DCSL-1, ECAR-1, ECAR-2, ECCD-1, ECCD-2

Check Content:

1. Check with your IOA or Systems Programming personnel and compile the list of BMC CONTROL-O Installation Datasets. Most likely they are similar to
SYS2.IOA.*.CTO*.** or SYS3.IOA.*.CTOI.**.
2. From the Administrator Main Menu Choose Option 2
Security Server
Commands.
3. Then choose Option: 3 Data Set.
4. Type the resource names collected in option a.1 above into:
'Enter fully
qualified (without quotes) data set or profile name:'.
5. Hit enter.
6. Enter Y for Display covering profile?
7. Verify that the UACC is NONE.
8. Verify that Audit Successes and Failures specifies UPDATE
or READ.
9. Tab down to Standard Access Permits and place an E next to
it (hit enter) and
validate that UPDATE or higher access is limited to Systems
Programming
personnel. Verify Read access if applicable is given to:

Auditors
BMC Users
BMC STCs
Batch Users.

10. If Conditional Access Permits: _ (E to edit data) has *data is

present* next to it, place an E next to it and validate that conditional access

permits of Update or higher are limited to Systems

Programming Personnel as

well. Verify Read access if applicable is given to:

Auditors
BMC Users
BMC STCs
Batch Users.

11. Repeat steps 2 through 10 for all datasets in option 1. above.

12. If 7, 8, 9 and 10 are all true, there is NO FINDING.

13. If 7, 8, 9 and 10 are not true, this is a FINDING.

Fix Text: The IAO will ensure that update and alter access to BMC CONTROL-O installation data sets is limited to System Programmers only, and all update and allocate access is logged. Read access can be given to all authorized users.

The installing Systems Programmer will identify and document the product data sets and categorize them according to who will have update and alter access and if required that all update and alter access is logged. He will identify if any additional groups have update and/or alter access for specific data sets, and once documented he will work with the IAO to see that they are properly restricted to the ACP (Access Control Program) active on the system.

Data sets to be protected will be:

SYS2.IOA.*.CTO*.**

SYS3.IOA.*.CTOI.**

The following commands are provided as a sample for implementing data set controls:

```
ad 'SYS2.IOA.*.CTO*.**' uacc(none) owner(sys2) -
audit(success(update) failures(read)) -
data('Vendor DS Profile: BMC CONTROL-O')
pe 'SYS2.IOA.*.CTO*.**' id(<syspau<dt>) acc(a)
pe 'SYS2.IOA.*.CTO*.**' id(<audtaudt> <bmcuser>)
pe 'SYS2.IOA.*.CTO*.**' id(<CONTROLO> <bmcbatch>)
pe 'SYS2.IOA.*.CTO*.**' id(*) acc(r)
```

```
ad 'SYS3.IOA.*.CTOI.**' uacc(none) owner(sys2) -
audit(success(update) failures(read)) -
data('Vendor DS Profile: BMC CONTROL-O')
pe 'SYS3.IOA.*.CTOI.**' id(<syspau<dt>) acc(a)
pe 'SYS3.IOA.*.CTOI.**' id(<audtaudt> <bmcuser>)
pe 'SYS3.IOA.*.CTOI.**' id(<CONTROLO> <bmcbatch>)
```

```
pe 'SYS3.IOA.*.CTOI.**' id(*) acc(r)
```

```
setr generic(dataset) refresh
```

CCI: CCI-000213

CCI: CCI002234

Group ID (Vulid): V-17067

Group Title: ZB000001

Rule ID: SV-31944r1_rule

Severity: CAT II

Rule Version (STIG-ID): [ZCTOR001](#)

Rule Title: BMC CONTROL-O STC data sets are not properly protected.

Vulnerability Discussion: BMC CONTROL-O STC data sets have the ability to use privileged functions and/or have access to sensitive data. Failure to properly restrict access to these data sets could result in violating the integrity of the base product which could result in compromising the operating system or sensitive data.

IAControls: DCSL-1, ECAR-1, ECAR-2, ECAR-3, ECCD-1, ECCD-2

Check Content:

1. Check with your ISSO or Systems Programming personnel and compile the list of BMC Control-O STC and/or batch data

sets datasets. Most likely they are similar to
SYS3.IOA.*.CTDO.**.

2. From the Administrator Main Menu Choose Option 2
Security Server Commands.

3. Then choose Option: 3 Data Set.

4. Type the resource names collected in option 1 above into:
"Enter fully qualified (without quotes) data set or profile name:
".

5. Hit enter.

6. Enter Y for Display covering profile?

7. Verify that the UACC is NONE.

8. Tab down to Standard Access Permits and place an E next to it (hit enter)and validate that UPDATE or higher access is limited to Systems Programming Personnel. Update access is permitted to BMC STCs, BMC Users and BMC batch users. Verify Read access is limited to Auditors, System Operators, and domain level Production Control and Scheduling personnel.

9.If Conditional Access Permits: _ (E to edit data) has *data is present* next to it, place an E next to it and validate that conditional access permits of UPDATE or higher are limited to Systems Programming Personnel. Update access is permitted to BMC STCs, BMC Users and BMC batch users. Verify Read

access is limited to Auditors, System Operators, and domain level Production Control and Scheduling personnel.

10. Repeat steps 2 through 9 for all datasets in option 1. above.

11. If 7, 8, and 9 are all true, there is NO FINDING.

12. If 7, 8, or 9 are not true, this is a FINDING.

Fix Text: The ISSO will ensure that UPDATE or higher access to BMC CONTROL-O STC data sets is limited to System Programmers. UPDATE access can be given to BMC STC(s) and/or batch user(s). Read access can be given to Auditors, System Operators, and domain level Production Control and Scheduling personnel.

The installing Systems Programmer will identify and document the product data sets and categorize them according to who will have update and alter access and if required that all update and alter access is logged. He will identify if any additional groups have update and/or alter access for specific data sets, and once documented he will work with the ISSO to see that they are properly restricted to the ACP (Access Control Program) active on the system.

Data sets to be protected will be:

SYS3.IOA.*.CTOO.**

The following commands are provided as a sample for

implementing data set controls:

```
ad 'SYS3.IOA.*.CTOO.**' uacc(none) owner(sys3) -
audit(failures(read)) -
data('BMC CONTROL-O Operational & Respostory')
pe 'SYS3.IOA.*.CTOO.**' id(<syspau<dt>) acc(a)
pe 'SYS3.IOA.*.CTOO.**' id(CONTROLO) acc(u)
pe 'SYS3.IOA.*.CTOO.**' id(<bmcuser> <bmcbatch>) acc(u)
pe 'SYS3.IOA.*.CTOO.**' id(<audtaudt>) acc(r)
```

setr generic(dataset) refresh

CCI: CCI-001499

Group ID (Vulid): V-17947

Group Title: ZB000020

Rule ID: SV-32062r1_rule

Severity: CAT II

Rule Version (STIG-ID): [ZCTOR020](#)

Rule Title: BMC CONTROL-O resources are not properly defined and protected.

Vulnerability Discussion: BMC CONTROL-O can run with sensitive system privileges, and potentially can circumvent system controls. Failure to properly control access to product resources could result in the compromise of the operating system environment, and compromise the confidentiality of customer data. Many utilities assign resource controls that can be granted to system programmers only in greater than read

authority. Resources are also granted to certain non systems personnel with read only authority.

IAControls: ECCD-1, ECCD-2

Check Content:

Verify that the accesses to resources in the BMC CONTROL-O Resources table in the zOS STIG Addendum are properly restricted.

Note: To determine what resource class is used review the IOACCLASS setting in SECPARM to determine the resource class to use. Refer to ZIOA0040 for this setting.

a) Verify the resources identified in the BMC CONTROL-O Resources table in the zOS STIG Addendum are properly defined and access is restricted to the appropriate personnel. For all the PROFILES found in BMC CONTROL-O Resources table in the zOS STIG Addendum:

1. From the Administrator Main Menu Choose Option 3
Security Server Reports
2. then choose Option: 4 General Resource Profile
3. On the command line chose option 4 AND then Put (* or \$\$*)
next to PROFILE: and (class name from ZIOA0040) next to CLASS:

Profile: from table (or specify \$\$* as all profile start with a \$\$)
Class: from ZIOA0040

4. Hit enter.
 5. Verify that the UACC for all profiles listed is NONE
 6. Place an S next to the profile and validate that the access list is appropriate (as defined or more restrictive than the BMC CONTROL-O Resources table in the zOS STIG Addendum.
If TYPE is GROUP, place an S in the CMD line and hit enter to explode the GROUP.
 7. For all resources with logging requirements place an LR next to the profile (hit enter and review the output) and validate that it specifies ALL(READ).
- b) If all profiles, access lists, and Auditing are defined like or more restrictive than the BMC CONTROL-O Resources table in the zOS STIG Addendum, then there is NO FINDING.
- c) If any Profile, Access list or Auditing is more permissive than the BMC CONTROL-O Resources table in the zOS STIG Addendum, then there is a FINDING.

Fix Text: The systems programmer will work with the IAO to verify that the following are properly specified in the ACP.

Ensure that the BMC CONTROL-O resources are protected as specified in the BMC CONTROL-O Resources table in the zOS STIG Addendum. This will include access by authorized users and logging requirements.

Sample:

```
rdef $ioa <controloresource>.** uacc(none) owner(admin)
audit(<see table in addendum>)
pe <controloresource>.** cl($ioa) id(<authorizeduser>)
acc(<accesslevel>)
```

CCI: CCI-000035

CCI: CCI-002234

Group ID (Vulid): V-17452

Group Title: ZB000030

Rule ID: SV-32074r1_rule

Severity: CAT II

Rule Version (STIG-ID): [ZCTOR030](#)

Rule Title: BMC CONTROL-O Started Task name is not properly identified / defined to the system ACP.

Vulnerability Discussion: BMC CONTROL-O requires a started task that will be restricted to certain resources, datasets and other system functions. By defining the started task as a userid to the system ACP, It allows the ACP to control the access and authorized users that require these capabilities. Failure to properly control these capabilities, could compromise of the operating system environment, ACP, and customer data.

IAControls: ECCD-1, ECCD-2

Check Content:

- a) From Analyzer main Menu, go to 3;4; Press ENTER
- b) Key in SORT PROCNAME; Press ENTER
- c) Key in L CONTROLO; Press ENTER
- d) If not found then CONTROLO; is not defined to RACF as a STC user.
- e) If found then use the U line command to determine if the userid is defined to RACF.
- f) The userid is defined to RACF if a userid display appears. If not defined
you should see the message No data to display.
- g) now press f3 to go back to the previous display. If no R is next to the entry then the user is protected.
- h) If an R is next to the entry, place an M on the command line and validate the following is NOT displayed:
VSA346R The user ID does not have the protected attribute.
- i) If the userid for the CONTROL-O started task is defined to the
security database and is protected, there is NO FINDING.
- j) If the userid for the CONTROL-O started task is not defined to
the security database, or is defined but does not have the protected attribute, this is a FINDING.

Fix Text: The BMC CONTROL-O system programmer and the IAO will ensure that a product's Started Task(s) is properly Identified / defined to the System ACP.

If the product requires a Started Task, verify that it is properly defined to the System ACP with the proper attributes.

Most installation manuals will indicate how the Started Task is identified and any additional attributes that must be specified.

A sample is provided here:

```
au CONTROLO name('stc, BMC CONTROL-O') owner(stc)
dfltgrp(stc) nopass
```

CCI: CCI-000764

Group ID (Vulid): V-17454

Group Title: ZB000032

Rule ID: SV-32175r1_rule

Severity: CAT II

Rule Version (STIG-ID): [ZCTOR032](#)

Rule Title: BMC CONTROL-O Started task is not properly defined to the STARTED resource class for RACF.

Vulnerability Discussion: Access to product resources should be restricted to only those individuals responsible for the application connectivity and who have a requirement to access these resources. Improper control of product resources could potentially compromise the operating system, ACP, and customer data.

IAControls: ECCD-1, ECCD-2

Check Content:

a) Use Vanguard's Analyzer product to look at the Started Procedures Analysis report:

1. From Analyzer main Menu, go to 3;4; Press ENTER
2. Key in SORT PROCNAME; Press ENTER
3. Key in L CONTROLO or the name of the CONTROLO started task; Press ENTER
4. Look at the source column. It will indicate STARTED class profile or ICHRIN03 entry.
5. If not found then the CONTROLO started task is not defined to RACF as a STC user.

b) If a STARTED resource class profile exists for the CONTROLO STC, there is NO FINDING.

c) If neither a STARTED resource class profile or an ICHRIN03 entry exists for the CONTROLO STC, this is a FINDING.

Fix Text: The BMC CONTROL-O system programmer and the IAO will ensure that a product's Started Task(s) is properly Identified / defined to the System ACP.

A unique userid must be assigned for the CONTROLO started task thru a corresponding STARTED class entry.

A sample set of commands is shown here:

```
rdef started CONTROLO.** uacc(none) owner(admin)  
audit(all(read)) stdata(user(CONTROLO) group(stc))  
setr racl(started) ref
```

CCI: CCI-000764

UNCLASSIFIED